



## PLC-WXU300

- Automatic set-up enables operation within seconds
- Projector with built-in 7 Watt speakers
- Black-board mode for optimised projections onto coloured surfaces
- WXGA Resolution (1,280 x 800) in 16 : 10 format
- Brightness: 2,500 ANSI lumens, contrast ratio: 500 : 1
- Security features: PIN code lock, key lock function
- Fan Noise: 29 dB (eco mode)
- 3 years warranty, 1 year lamp warranty

## PLC-WXU300

TECHNICAL DATA	PLC-WXU300
Category	Business & Education
Panel	3 x 0.59 " TFT p-Si (16:10), micro lens
Panel type	Organic LCD panel
Lamp	225 W UHP (LMP-131)
Brightness	2500 ANSI lumens
Brightness (eco mode)	1750 ANSI lumens
Lamp life	2500 h (eco mode) / 2000 h (normal mode)
Fan noise	29 dB (eco mode) / 34 dB (normal mode)
Standard lens	F = 1.65 - 2.33 / f = 15.47 - 24.53 mm *
Throw Distance Ratio	1.18 - 1.91 : 1
Throw Distance	0.74 - 7.67 m
Contrast ratio	500 : 1
Resolution in pixels	1,280 x 800 (W-XGA)
Image size min. - max. (diagonal):	30 - 300 inch
Uniformity	85 %
Bandwidth/Frequency	140 MHz, Horizontal : 15 - 100 kHz, Vertical : 50 - 100 Hz
Colour systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: D-Sub15 (RGB/Component/SCART-RGB) Input 2: HDMI (HDCP) Input 3: RCA (Composite) Input 4: Mini DIN 4 (S-Video) Audio: 3.5 mm Stereo Jack Audio: 2 x RCA (R/L mono) Audio output : 3.5 mm Stereo Jack Monitor output: D-Sub15 Control Input Jack 1: D-Sub9 (RS232) Control Input Jack 2: RJ45 (LAN)
Audio function	7 W mono
Keystone correction	vertical +/- 30°
Up/Down Ratio	49:1 (Fixed U/D Ratio)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,035i, 1,080i
Computer compatibility	U-XGA, S-XGA, S-XGA+, W-XGA, XGA, S-VGA, VGA, WXGA+, WSXGA+, WUXGA
Zoom/Focus	1.6 x/manual
Power consumption	213 W (eco mode) / 291 W (normal mode), 0.8 W (stand-by mode)
Voltage	100 - 240 V
Warranty	3 years, 24-hr replacement service (D/CH/I/F - except overseas), 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	326.0 x 92.6 x 265.2 mm
Weight (Net)	2.8 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Carrier bag, Lens cap, CD-ROM for network module
Optional accessories	Components/D-Sub15 cable (POA-CA-COMPVGA), SCART/D-Sub15 cable (POA-CA-SCART), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03)
Lenses	Standard lens

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 05/2009

